



## Enquiry/Order Form - Ancon Keybox

Please provide product requirements and contact details. For orders please complete delivery details here:

Date Order Enquiry Company Address				F	Delivery Date Project Delivery Address			
State Contact Tel		Post Code			State Post Code Site Contact Tel			
Email  B  Type U U Bar (not available in		C T	P P Cog Bars	 	Type JL Cog I	Bars	C C C	P. Cog Bars
C Per		E P			B P  Type AA Double Straight Bars			
Type L Cog Ba	36	880	ype A Straight Bar		36 96 1991 1992 1991 1992 1993 1994 1995 1995 1995 1995 1995 1995 1995	36	178	36
Reference	Quantity	Box Width (mm) (see above)	Bar Arrangement (see above)	Spacing (mm)	Box Length (mm) (see note 1)	Embedment E (mm) (see note 2)	Pullout P (mm) (see note 3)	Cog Length C (mm) (see note 4)
Re-bending Tool		Important: Bars must be straightened using a Keybox re-bending tool. Re-bend in one smooth motion.  Do not straighten bars more than once.						

- (1) Standard box lengths 800mm, 1000mm and 1200mm.
- (2) Minimum Embedment (E) of 130mm for U, L and J types and 535mm for A and AA types unless specified otherwise.
- (3) Standard pullout (P) 480mm, others available subject to limitations of box length.
- (4) Standard 170mm cog length for types L and J. Other cog lengths available.
- (5) The Ancon Keyboxes are all manufactured from N12 reinforcement bar.

